

Series 162A Disposable Plastic Spiral Bell High Flow Mixer



Intended for high flow rate meter mix applications, this series contains our largest disposable bell mixers: 0.784 inches in diameter with either 16, 23, 32, 39 or 48 elements.

The rugged nylon housing has an oversized bell inlet. The downstream outlet is designed with a 1/2" NPS male thread to attach extensions or other types of accessories.

Specification

- Elements: Acetal
- Housing: Nylon

Accessories

- Manifold
- Retaining Nut
- One-Piece Metal Jacket



Part #	# Mixing Elements	Element Diameter (inch/mm)	Element Length (inch/cm)	Outside Diameter (inch/mm)	Pressure Limit (Psi@75°F / Bar@30°C)
7701057	16	0.784 / 19.9	12.5 / 31.7	0.98 / 24.9	580 / 39
7701059	23	0.784 / 19.9	17.0 / 43.2	0.98 / 24.9	580 / 39
7701063	32	0.784 / 19.9	24.5 / 62.2	0.98 / 24.9	580 / 39
7701066	39	0.784 / 19.9	30.3 / 77.0	0.98 / 24.9	580 / 39
7701067	48	0.784 / 19.9	36.4 / 92.5	0.98 / 24.9	580 / 39
7362603	64	0.784 / 19.9	48.5 / 123.2	0.98 / 24.9	580 / 39



EFD

For Nordson EFD sales and service in over 40 countries, contact Nordson EFD or go to www.nordsonefd.com.

Global

800-556-3484; +1-401-431-7000
info@nordsonefd.com

Europe

00800 7001 7001
infoefd.europe@nordsonefd.com

Asia

China: +86 (21) 3866 9006; china@nordsonefd.com
India: +91 80 6546 8719; india@nordsonefd.com
Japan: +81 03 5762 2760; japan@nordsonefd.com
Korea: +82-31-736-8321; korea@nordsonefd.com
SEAsia: +65 6796 9522; sin-mal@nordsonefd.com

©2024 Nordson Corporation v111424



more info