

# BKG® Optigon™

## Underwater Pelletizing System

Throughput range up to ≤15,000 kg/hr (33,000 lb/hr)

### Processes

- Polymerization
- Masterbatch
- Compounding
- Recycling

### Materials

- All materials which behave like thermoplastic polymers (PE, PP, PS, ABS, SAN, PA, PET, PC, POM, TPE, TPU, EVA, APAO, PBT, PMMA, EPDM)
- Highly-filled compounds
- Materials which generate a high degree of fines



### Features

- Polygon™ automatic filter + secondary filtration
- Self-cleaning tempered water system
- Modular design
- Completely skid-mounted
- Noise reduction of the pellet dryer ≤ 80 dB(A)
- Large dryer door for easy access
- Pre-dewatering
- Dryer available with inspection window and lights
- Cleaning system for the pellet dryer available
- Larger systems upon request

### Benefits

- Continuous, automatic water filtration
- High level of automation, reduced operator intervention
- Improved water filtration level (up to 70µm)
- Optional belt filter maximizes system automation
- Energy savings during operation through elimination of secondary pump
- Premium options / features available
- Process water tank can be heated via steam or other medium versus electrical heating
- Explosion protected design according to ATEX available

Model	Pellet Dryer	Capacity
Optigon™ 2	TVE 2004 SR	< 2,500 kg/hr (5,500 lb/hr)
Optigon™ 3	TVE 6002 SR	< 5,000 kg/hr (11,000 lb/hr)
Optigon™ 4	TVE 6002 SR	< 7,500 kg/hr (16,500 lb/hr)
Optigon™ 5	TVE 12000 SR	≤ 15,000 kg/hr (33,000 lb/hr)

**Nordson BKG GmbH**  
Hessenweg 3-5  
48157 Münster / Germany  
**Phone** +49.251.26501.0

**USA**  
**Phone** +1.828.326.9888

**China**  
**Phone** +86.21.5785.091.8

**Japan**  
**Phone** +81.3.5762.2770



nordsonpolymerprocessing.com | info@nordsonpolymerprocessing.com

© 2021 Nordson BKG GmbH  
Printed in USA  
01/2021

BKG is a trademark of Nordson Corporation,  
registered in the United States and other countries.