

# BKG<sup>®</sup> Master-Line<sup>™</sup>

## Underwater Pelletizing System

Throughput range up to 2,000 kg/hr (4,400 lb/hr)

### Processes

- Masterbatch
- Compounding
- Recycling

### Materials

- All materials which behave like thermoplastic polymers (PE, PP, PS, ABS, SAN, PA, PET, PC, POM, TPE, TPU, EVA, APAO, PBT, PMMA, EPDM)



### Features

- Modular design
- Completely skid-mounted
- Dual door dryer access for easy cleaning
- Robust design and equipped with all the essentials

### Benefits

- Our entry-level underwater pelletizing system
- Compact footprint
- Flexibility for material and / or color changes
- Easy and fast cleaning of the system components
- Easy operation, simple handling

Model	Pellet Dryer	Capacity
Master-Line <sup>™</sup> 300	TVE 1001 ED	< 500 kg/hr (1,100 lb/hr)
Master-Line <sup>™</sup> 2000	TVE 2000 ED	< 2,000 kg/hr (4,400 lb/hr)

**Nordson BKG GmbH**  
Hessenweg 3-5  
48157 Münster / Germany  
Phone +49.251.26501.0

**USA**  
Phone +1.828.326.9888

**China**  
Phone +86.21.5785.091.8

**Japan**  
Phone +81.3.5762.2770