

Series 140 In-line Plastic Mixers

Ideal for one-use fluid dispensing



This all-plastic assembly is ideal for short pot life adhesives. Its low cost allows disposal of the mixer instead of purging or baking. The housing is translucent, so the operator can inspect the condition of the mixer. With the interior mixing elements molded of Acetal, it has the toughness and chemical resistance to be inert to common solvents. Maximum Service temperature is 250° F (121° C).

Specification

- Elements: Acetal, non-removable
- Housing: Nylon or nylon with brass threaded ends

EFD's disposable static mixers eliminate the need to worry about premature curing of materials.

Part #	# Mixing Elements	Element Diameter (inch/mm)	Housing Ends (mnpt)	Housing Length (inch/cm)	Outside Diameter (inch/mm)	Pressure Limit (Psi@75°F / Bar@30°C)
7700712	18	0.370 / 9.40	1/4"	9.60 / 24.38	0.500 / 12.70	460 / 32
7700715	30	0.370 / 9.40	1/4"	13.50 / 34.29	0.500 / 12.70	460 / 32
7700737	12	0.497 / 12.62	3/8"	8.50 / 21.59	0.630 / 16.00	350 / 24
7700738	18	0.497 / 12.62	3/8"	11.10 / 28.19	0.630 / 16.00	350 / 24
7700773	24	0.784 / 19.91	3/4"	20.40 / 51.82	0.920 / 23.37	240 / 17
7700776	32	0.784 / 19.91	3/4"	25.60 / 65.02	0.920 / 23.37	240 / 17



EFD

For Nordson EFD sales and service in over 40 countries, contact Nordson EFD or go to www.nordsonefd.com.

Global

800-556-3484; +1-401-431-7000
info@nordsonefd.com

Europe

00800 7001 7001
infoefd.europe@nordsonefd.com

Asia

China: +86 (21) 3866 9006; china@nordsonefd.com
India: +91 80 4021 3600; india@nordsonefd.com
Japan: +81 03 5762 2760; japan@nordsonefd.com
Korea: +82-31-736-8321; korea@nordsonefd.com
SEAsia: +65 6796 9522; sin-mal@nordsonefd.com

©2024 Nordson Corporation v111424



more info