OptiMixer Series 480 Disposable Mixers

Optimized mix performance in a significantly shorter length



The Nordson EFD OptiMixer provides better mix quality in a shorter length.



SmartLok adapters are designed to adapt Nordson EFD OptiMixer mixers to F-System Side x Side cartridges.

The OptiMixer's unique, patented design incorporates material flow path improvements and redesigned wedge elements. Both contribute to significantly improved mix quality in a length that's about 20% shorter than comparable square mixers – the shortest in the marketplace.

The mixer's shorter length allows users to dispense two-component materials within closer proximity to applications, providing greater control and higher job quality.

Nordson EFD used proprietary flow simulation technology to optimize the design of the cross flow inverters and element wedges. The result is a high-performance mixer that produces the best quality mix with less retained volume. The Series 480 mixer elements are 8.7 mm wide.

OptiMixer[™] attaches to most large volume, multi-ratio cartridges including EFD's u-TAH[®] Universal, Side x Side, and 380mL Coaxial cartridges.

Features

- Improved material flow path design the next step in the evolution of EFD's patented flow inverter
- Redesigned wedge elements a significant improvement over our patented single-wedge design
- Available with Nordson EFD SmartLok[™] adapter to fit F-System Side x Side cartridges

Benefits

- Improved mixing in a shorter length without impacting performance factors
- 30% less retained volume than comparable mixers for reduced fluid waste
- Improved adhesive bond strength





Specifications

SERIES 480 OPTIMIXERS						
Element Width 0.344 / 8.7 (in/mm)						
Part #	# Mixing Elements	Housing Length (inch/cm)	Housing Inlet*	Housing Outlet	Retained Volume (ml)	Element / Housing
7361685***	9	2.9 / 7.4	Integral Nut	Barbed	1.6	Acetal / PP
7361689	17	4.0 / 10.2	Integral Nut	Stepped	4.7	Acetal / PP
7361695	25	5.1 / 13.0	Bell**	Stepped	6.5	Acetal / PP
7361697	25	5.6 / 14.2	Integral Nut	Stepped	6.5	Acetal / PP
7361703	33	6.3 / 16.0	Bell**	Stepped	7.5	Acetal / PP
7361705	33	6.8 / 17.3	Integral Nut	Stepped	7.5	Acetal / PP
7361707	41	8.1 / 20.6	Integral Nut	Stepped	10.0	Acetal / PP

*Housing Inlet for OptiMixers assembled with SmartLok adapters are separated bore and color-coded by ratio

** Needs retaining nut #7702598

*** In prototype



For Nordson EFD sales and service in over 40 countries, contact Nordson EFD or go to www.nordsonefd.com.

Global

800-556-3484; +1-401-431-7000 info@nordsonefd.com

Europe

00800 7001 7001 infoefd.europe@nordsonefd.com

Asia

China: +86 (21) 3866 9006; china@nordsonefd.com India: +91 80 4021 3600; india@nordsonefd.com Japan: +81 03 5762 2760; japan@nordsonefd.com Korea: +82-31-736-8321; korea@nordsonefd.com SEAsia: +65 6796 9522; sin-mal@nordsonefd.com

©2024 Nordson Corporation v010424