Control Coat® QE Applicators

Precise non-contact applicator optimizes hot melt material coating.

Control Coat QE applicators:

- Deliver uniform patterns and stronger, repeatable bonds
- Enhance product features: breathability, permeability and softness
- Provide exceptional control of side, leading and trailing edges
- Apply non-contact fibrous coatings on irregular surfaces



Control Coat applicators increase production capabilities and flexibility in high-speed continuous or intermittent processes often seen in nonwoven or web coating applications. The non-contact delivery allows use with a wide variety of substrates including heat-sensitive ones, as the adhesive cools before contact.

The Control Coat applicator uses low-volume, high-velocity heated air to fiberize adhesive as it is dispensed. These fine adhesive particles are then precisely deposited on the substrate resulting in a consistent, uniform pattern.

Superior cutoff and reduction of overspray provide for excellent edge control, improving product quality while reducing machine contamination and minimizing adhesive waste. The air distribution method reduces web disruption and provides uniform adhesive coverage even on porous or irregular substrates.

The compact design fits easily into existing or new production lines and the Control Coat applicator can be customized to meet specific customer requirements. Various quick-exchange components simplify and speed-up maintenance and changeovers.



Control Coat® QE Applicators

Specifications

Operating Temperature 200° C (392° F) maximum Application Width 5 to 475 mm (0.2 to 18.7 in.)


Temperature Sensors Ni120 or PT100

Spray Air Pressure 0.8 to 1.5 bars (11 to 22 psi)

Maximum Cycles 9,000 cycles/minute

Control Voltage 24 VDC

Electrical Requirements 230 VAC, 50/60 Hz



Quick-exchange filter, module and nozzle

For more information, speak with your Nordson representative or contact your Nordson regional office.

United States

Duluth, Georgia (800) 683-2314 **Phone** (866) 667-3329 **Fax**

Europe

Luneburg, Germany (49) 4131-894-0 **Phone** (49) 4131-894-149 **Fax**

Japan

Tokyo, Japan (81) 3-5762-2700 **Phone** (81) 3-5762-2701 **Fax**

Asia/Australia/ Latin America

Amherst, Ohio (440) 985-4496 **Phone** (440) 985-1096 **Fax**

Find us on:









NWL-14-5853 Issued 7/14 © 2014 Nordson Corporation All Rights Reserved. Printed in U.S.A. Nordson reserves the right to make design changes between printings.



